



Effective Date: 22 August 2005

Revision Date: N/A

Revision: 000

## **ROTO-BRITE® L-2746I TECHNICAL DATA SHEET**

---

### **CLEANING COMPOUND FOR ALL METALS WITH INHIBITOR**

#### **APPLICATION:**

LIQUA-BRITE® L-2746I is a cleaning compound, with added corrosion inhibitors, used with all metals to provide clean, light-colored surfaces. It is effective with ceramic, resin-bonded, natural stones, and fused aluminum oxide media and is able to defoam resin-bonded media. Recommended usage rate is ½ to 4 ounces per gallon of water or 1 ½ to 3% at 120 – 160° F to clean stubborn oils as a spray wash compound.

#### **CHARACTERISTICS:**

- Excellent cleaning of parts
- Imparts light metal color
- Low to medium foam level
- Effective in hard water
- Corrosion inhibition of non-ferrous parts

#### **PROPERTIES:**

- Straw-colored to amber liquid
- Reactivity: pH of 100% solution = 9.9; pH of 1% solution = 8.9
- Density 1.085 gm/cc; 9.04 pounds/gallon
- Biodegradable and Formulated without phosphates, chromates or nitrites

#### **FIRST AID:**

Should contact occur, wash area with plenty of water. For eyes, flush with water and seek medical attention immediately.

#### **CAUTION:**

LIQUA-BRITE® L-2746I is an industrial grade product. Avoid excessive contact with skin, eyes, or clothing.

The data presented are believed accurate. Roto-Finish Company, Inc. can guarantee only its product. User must verify suitability to his own application.

KJE:jh 08/22/05



1600 Douglas Avenue • Kalamazoo, MI 49007  
(269) 345-7151 • FAX (269) 345-1710  
[SALES@ROTO-FINISH.COM](mailto:SALES@ROTO-FINISH.COM) • [WWW.ROTO-FINISH.COM](http://WWW.ROTO-FINISH.COM)



